A forum for woodworkers of all skill levels to share their common interests

Northwest Woodworkers' Guild

THE SAWDUST NEWS

April 2010

http://www.nwwguild.org

Next Meeting:

Leigh Dovetail Jig by Rick Tydings Thursday April 29, 2010 6:30 PM

Woodcraft Supply

5963 Corson Ave. S. Seattle WA 98108

Phone: (206) 767-6394

Guild Officers

President—Bob Schaefer

Vice-president and
Membership—Sally Wright
Treasurer—Chris Green
Secretary—Rick Tydings
Programs—Al Falco, Don
McNutt, Jack Martin, Ed
Moore, Ray Ross
Raffle—Tom Murray, Herb
Stoops
The following are volunteer
positions and are not
Officers of the Guild:

Webmaster

Tom Howorth thoworth@gmail.com


Newsletter

Steve Krauss catbert@oz.net 425-746-5067

President's Message

- by Bob Schaefer

"Brevity is the soul of wit". Hamlet, act 2 scene 2, lines 86-92





Fred Floyd made an excellent and informative presentation. Thank you Fred. See the secretary's meeting notes for additional details.

Again thanks to Ron Hall and Woodcraft Supply for providing a great meeting place,

Next meeting will be at Woodcraft Supply April 29 at 6;30. I will not be able to attend. Rick Tydings will conduct the meeting and will also present the program. Come with suggestions for future meetings.

March Meeting Minutes:

Northwest Woodworkers business meeting consisted of Chris Green reporting \$2,342 in treasury and Sally Wright reported we have 92 paid members. The raffle consisted of magazines from Charlie Culler and a 3rd Hand devise from Woodcraft. Dennis Harrison shared his Tree inlay project, and announced a Flower Arrangement Show at Embassy Suites, 3225 158th Ave SE in Bellevue from 12 AM to 3 PM on April 24th.

The highlight of the meeting was Fred Floyd presenting the construction of a Sam Maloof style rocking chair. Fred walked us thru the process where he spent 100 hours building and assembling this beautiful rocking chair made of cherry wood. He discussed the joinery, lamination, curves, grinding and sanding, screw joints, jig assembly and special compound cuts. For those interested in further information you may contact HalTayler.com or RockingChairs.net Our sincere appreciation goes to Fred Floyd for the wonderful presentation!!!

Next Meeting:

The Northwest Woodworkers April 26th Meeting will be held at Woodcraft starting at 6:30 PM. Rick Tydings will use the Leigh Dovetail Jig and demonstrate the Inlayed Dovetail process, additionally we will spend a little time discussing future meeting topics. Members are requested to bring ideas and sources for up coming meetings.

A forum for woodworkers of all skill levels to share their common interests



Northwest Woodworkers Guild Steve Krauss, Newsletter Editor 16204 Main St Bellevue, WA 98008

Member's Discounts

All members in good standing receive a membership card that will allow them to get a discount at the stores listed below:

Crosscut Hardwoods

4100—1st Avenue S., Seattle 98134 10% Discount

Rockler Woodworking 3823 Stone Way N. Seattle 98103

10% Discount (not valid on power tools)

Woodcraft Supply 5963 Corson S., Seattle 98108 10% Discount (not valid

on power tools or workbenches)

Edensaw Woods 8032 S. 194th St. Kent, WA 98032

Please present your current membership card to receive your discount.

Monthly Shop Tip Contributed by Herb Stoops

CAULKING GUN MAKES A SURE-SHOOTIN' HOLD-DOWN HARDWOOD CHANNEL DETAIL 31/5" 3/4 x 13/4 x 18" hardwood channels 3/4 x 27/16 x 4" slide block #8 x 2" F.H. #8 x 2" F.H % x 31/2 x 24" brass wood screw 31/2" *Or, so slide block slides freely Notch rear fence to match shape of wooden CLAMP DETAIL Open caulking gun handle. channels. Bend tabs inserting through slots. 11/2"-thick saw blade guard Cut off #8 x 3/4" F.H. 3/4 x 5/16 x 191/2" hardwood miterexcess gun wood screw parts. (centered over blade path) Hole drilled for gun shaft gauge guide strip #8 x 3/4" P.H. wood screw 3/4 x 191/2 x 24" plywood base Re-attach pad after assembly. When designing a panel-cutting jig wood block, as shown in the accomodate gun. for my tablesaw, I wanted a way to Clamp detail drawing inset. Nylon nut firmly clamp a workpiece in the jig. The block moves back and UHMW self-adhesive on end of pad I found the solution in the paint forth in a channel on the panel department of a discount store. jig, which I built as shown. I bought an ordinary bar-style To use the clamp, I simply caulking gun for less than \$3, slide it over my workpiece. A few threaded off the nylon nut that quick squeezes of the trigger holds the plunger pad to the rod, secures the piece for a safe cut. and attached the clamp to a hard--Rusty Bentzinger, Leighton, Iowa

MAKE STRONGER DOORS WITH YOUR TABLESAW

When building frame-and-panel doors, I make them extra strong by making the tenons long. Rather than chisel out the deep mortises, you can cut them on a tablesaw. In the stile, center a ¼"-deep groove for the panel with your dado blade. Then, raise the tablesaw cutting depth up to I". Measure the width of your tenon, and clamp a stopblock to your tablesaw fence, as shown at far right. Then, run the stile groove-side down over the dado blade to the stopblock.

-Erv Roberts, Des Moines, Iowa

